

TX7812

Graphical Monitor Centre Software



Feature and Benefits

- Easy to use, direct and complete fire alarm graphic software
- Auto Display of all kinds of event such as Fire, Pre-alarm, Action, Supervisory, Disable and Fault in different color.
- Display the full device details, time of alarm and location and save directly maintenance record folder.
- Multiple users can monitor and control at the same time
- User privileges can be defined
- Support remote control of control panel
- Support common toolbar for quick operation
- Support up to 8 client users

Overview

With TX7004 controller design a new set of software engineering monitoring system, provide software architecture designed to meet various requirements of stand-alone monitoring system, network and other aspects of the system, the system is easy to operate and interface.

The graphic display device relates to the fire alarm controller through the USB port, and relates to the remote monitoring clients through TCP/IP LAN topology, so as to realize the real-time monitoring of the fire alarm controller and the field equipment information.

System Components

Graphical display device software is composed of two parts, server and clients. Server as a bridge between the controller and the client, is mainly used to manage communications between the client and the controller, set user permissions, verify the legitimacy of the user, and record user login information, and a controller connection status. The client is mainly used to receive the status information of the field equipment which is uploaded by the controller. It is displayed in real time and classification and record the fire alarm information and the system operation log.

Technical Specification

Operating Software

CPU

RAM

HDD

System Type

Windows 7, 8 and Windows 10

P4 1G or Higher

2G

8G

32 or 64 Bit OS

