


# TX7708

## Fire Emergency Telephone



### Feature and Benefits

- 8 Zone addressable fire telephone center wall mounted Panel
- 2-way voice communication and can call panel to panel
- Each zone supports up to 5 fire phone station and Networkable up to 8 Fire Telephone panels
- Call divert feature to the main panel if slave panel do not attend the call
- Operator can ring outstations and fixed handsets and can select group call.
- Communication line and network cable monitoring
- Built-in Sounder and Mute button

### Technical Specification

#### Power Rating

Operating Voltage	24 VDC (External EN54-4 PSU is required)
Standby Current	150mA
Alarm Current	750mA Maximum

#### Capacity

Panel	Up to 8 zone
Panel to Panel	Up to 8 units
Panel to Fire Phone Station	Up to 5 Fixed and Hands-free or up to 7 jack points

#### Communication Signal

Frequency	300 to 3400 Hertz
Crosstalk	-60dB
Transmission Loss	5dB
End of Line Resistor	10kΩ±0.5KΩ
Communication Cable	Fire Rated 2x1.00mm <sup>2</sup> / less than 20ohms Impedance

#### Material / Colour

Dimension	400.5mm x 280mm x 100mm
IP Grade	IP30 Indoor Use
Gross Weight	4.2Kg

#### Operating Environment

Temperature	-5°C~+40°C
Relative Humidity	≤95%, non-condensing

